

IntePlus® CC Film

Cover and Tarpaulin

IntePlus® CC Film, is a very strong film with tough puncture resistant properties that is ideal for covers and tarps. IntePlus® CC Film can be produced with different levels of UV Inhibitors to deal with outdoor exposure.

Features:

- Extended durability even when exposed to high UV radiation
- Strong, tough, puncture resistant
- The strong 1-piece cover requires NO sealing or taping up to a width of 180" or with seam up to 360"
- Will not deteriorate - water and rot resistant
- Excellent protection against dirt and dust

Applications:

- Irrigation trench cover
- Winter swimming pool cover
- Vehicle and boat tarpaulin
- Cotton module cover
- Machine cover
- Grain and silage storage
- Cargo protection cover



Technical Data Sheet

Property	Test Method	Unit	Film Dir.	Typical Value	
Thickness	XFWI0201	GSM	--	125 ± 10%	150 ± 10%
		Mil	--	5.3 ± 10%	6.3 ± 10%
Yield	--	lb/msf	--	25.604	30.725
Tensile @ Ultimate	ASTM-D882	lb/in	MD	27	32
			TD	19	26
Elongation @ Ultimate	ASTM-D882	%	MD	600	700
			TD	600	700
Dart Impact	ASTM-D1709 (Method A)	grams	--	460	900
PP Tear	ASTM-D2582	grams	MD	8000	10000
			TD	9000	10000

Please note that the above information is to the best of our knowledge and is made without guarantee. These are typical property values and are intended as guides only, not as specification limits. We can not anticipate all conditions under which this information and our products, or products of other manufacturers in combination with our products may be used. Users are advised to conduct their own test and evaluation to determine the safety and suitability for their own purposes. We accept no responsibility for results obtained by the application of the information or the safety and suitability of our products. Issued Date: 12/17/07



OFFICE: 9 Peach Tree Hill Rd., Livingston, NJ 07039
 PLANT: 101 Inteplast Blvd., Lolita, TX 77971

TEL: 1-800-452-2117 1-973-994-8058, 8035, 8077

FAX: 1-800-709-6002

E-MAIL: inteplus@inteplast.com

WEB SITE: www.inteplast.com